

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

RECEIVED
CENTRAL FAX CENTER PATENT
AUG 28 2006 450100-03320

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application. An identifier indicating the status of each claim is provided.

Listing of Claims

1. (Previously Presented) A television receiver, comprising:
 - a selector for receiving television broadcasting signals, wherein the selector selects one of the television broadcasting signals;
 - a display element for displaying a video based on a video signal of the television broadcasting signal selected by said selector;
 - a storage device for storing program selection information to be used to control said selector and channel numbers in a coordinated relationship and storing program-related information,
 - said program-related information used for execution of object processing programs and the channel numbers in a coordinated relationship;
 - an acceptance device for accepting a selective input of a channel number from a user;
 - a readout device for reading out information corresponding to the channel number accepted by said acceptance device from said storage device;
 - a selection control device for controlling, when the information read out by said readout device is the program selection information, said selector based on the program selection information; and

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

a program execution device for executing, when the information read out by said readout device is the program-related information, a program in response to the program-related information;

wherein the television receiver is adapted to specify one or more channels associated with:

- a predetermined ISP;
- a processing program for preparation, transmission or reception of electronic mail;
- a transmission list of electronic mails;
- a reception list of electronic mails; and
- one or more accessed web pages.

2. (Original) The television receiver according to claim 1, wherein said acceptance device includes channel up/down keys for accepting selective inputs of the channel number in forward and reverse directions, respectively.

3. (Previously Presented) The television receiver according to claim 1, wherein the program-related information coordinated with at least one of the channel numbers relates to a processing program which can be executed by said television receiver.

4. (Previously Presented) The television receiver according to claim 1, further comprising:

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

a communication device for connecting said television receiver to a
communication network,

wherein the program-related information coordinated with at least one of the
channel numbers relates to a program to be executed to allow at least said television receiver to
transmit or receive information through said communication device.

5. (Previously Presented) The television receiver according to claim 1,
further comprising:

a communication device for connecting said television receiver to a
communication network, and

a received information storage device for storing received information received
through said communication device,

wherein the program-related information coordinated with at least one of the
channel numbers relates to a program to be executed to cause at least display information of the
received information stored in said received information storage device to be displayed on said
display element.

6. (Previously Presented) The television receiver according to claim 1,
further comprising:

a communication device for connecting said television receiver to a
communication network, and

a transmission information storage device for storing transmission information to
be transmitted through said communication device,

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

wherein the program-related information coordinated with at least one of the channel numbers relates to a program to be executed to cause at least display information of the transmission information stored in said transmission information storage device to be displayed on said display element.

7. (Previously Presented) The television receiver according to claim 1, further comprising:

a display information storage device for storing display information to be displayed on said display element,

wherein the program-related information coordinated with at least one of the channel numbers relates to a program to be executed to cause at least a video corresponding to the display information stored in said display information storage device to be displayed on said display element.

8. (Previously Presented) The television receiver according to claim 1, further comprising:

an instruction input acceptance device for accepting a display instruction input of a list of the information stored in said storage device; and

a list display signal formation device for forming, when an instruction to display the list is accepted by said instruction input acceptance device, a displaying signal for displaying the list of the information stored in said storage device on said display element.

9. (Previously Presented) The television receiver according to claim 8, further comprising:

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

a touched position detection device provided on a display screen of said display element for detecting a touched position of said display screen touched by a user,

wherein said readout device uses a channel number corresponding to a display item of the list displayed at the touched position of said display screen detected by said touched position detection device as a channel number selected by the user.

10. (Original) A television receiver according to claim 1, wherein said program execution device executes the program from a process which was being executed upon switching from a channel number to which the program is allocated to another channel number.

11. (Previously Presented) A receiver, comprising:

- a selector for receiving broadcasted signals and selecting one of the broadcasted signals;
- a signal outputting device for outputting a displaying signal of the broadcasted signal selected by said selector;
- a storage device for storing program selection information to be used to control said selector and channel numbers in a coordinated relationship and storing program-related information to be used for execution of object processing programs and the channel numbers in a coordinated relationship;
- an acceptance device for accepting a selective input of a channel number from a user;
- a readout device for reading out information corresponding to the channel number accepted by said acceptance device from said storage device;

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

a selection control device for controlling, when the information read out by said readout device is the program selection information, said selector based on the program selection information; and

a program execution device for executing, when the information read out by said readout device is the program-related information, a program in response to the program-related information;

wherein the television receiver is adapted to specify one or more channels associated with:

- a predetermined ISP;
- a processing program for preparation, transmission or reception of electronic mail;
- a transmission list of electronic mails;
- a reception list of electronic mails; and
- one or more accessed web pages.

12. (Original) The receiver according to claim 11, wherein said acceptance device includes channel up/down keys for accepting selective inputs of the channel number in forward and reverse directions, respectively.

13. (Previously Presented) The receiver according to claim 11, wherein the program-related information coordinated with at least one of the channel numbers relates to a processing program which can be executed by said receiver.

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

14. (Previously Presented) The receiver according to claim 11, further comprising:

a communication device for connecting said receiver to a communication network,

wherein the program-related information coordinated with at least one of the channel numbers relates to a program to be executed to allow at least said receiver to transmit or receive information through said communication device.

15. (Previously Presented) The receiver according to claim 11, further comprising:

a communication device for connecting said receiver to a communication network;

a received information storage device for storing received information received through said communication device, and

wherein the program-related information coordinated with at least one of the channel numbers relates to a program to be executed to cause a displaying signal corresponding to at least display information of the received information stored in said received information storage devices to be outputted from said signal outputting device.

16. (Previously Presented) The receiver according to claim 11, further comprising:

a communication device for connecting said receiver to a communication network; and

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

a transmission information storage device for storing transmission information to be transmitted through said communication device,

wherein the program-related information coordinated with at least one of the channel numbers relates to a program to be executed to cause a displaying signal corresponding to at least display information of the transmission information stored in said transmission information storage device to be outputted from said signal outputting device.

17. (Previously Presented) The receiver according to claim 11, further comprising:

a display information storage device for storing display information to be displayed on a display element,

wherein the program-related information coordinated with at least one of the channel numbers relates to a program for causing a displaying signal at least corresponding to the display information stored in said display information storage device to be outputted from said outputting device.

18. (Previously Presented) The receiver according to claim 11, further comprising:

an instruction input acceptance device for accepting a display instruction input of a list of the information stored in said storage device; and

a list display signal formation device for forming, when an instruction to display the list is accepted by said instruction input acceptance device, a displaying signal for displaying

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

the list of the information stored in said storage device and allowing the displaying signal to be outputted from said signal outputting device.

19. (Original) The receiver according to claim 11, wherein said program execution device executes the program from a process which was being executed upon switching from a channel number to which the program is allocated to another channel number.

20. (Previously Presented) A program execution method performed by an electronic apparatus which has a function of receiving broadcasting signals and selecting one of the broadcasting signals, comprising the steps of:

storing program selection information to be used to control channel selection and channel numbers in a coordinated relationship and program-related information to be used for execution of object processing programs and the channel numbers being stored in a coordinated relationship in a predetermined memory of said electronic apparatus;

accepting a selective input of a channel number from a user;

reading out information corresponding to the channel number accepted in the acceptance step from said predetermined memory;

controlling, when the information read out in the readout step is the program selection information, the channel selection based on the program selection information; and

executing, when the information read out in the readout step is the program-related information, a program in response to the program-related information;

wherein the predetermined memory includes a table adapted to specify one or more channels associated with:

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

a predetermined ISP;
a processing program for preparation, transmission or reception of
electronic mail;
a transmission list of electronic mails;
a reception list of electronic mails; and
one or more accessed web pages.

21. (Original) The program execution method according to claim 20, wherein,
in the step of accepting, selective inputs of the channel number are accepted successively in a
forward or reverse direction of the channel number.

22. (Previously Presented) The program execution method according to claim
20, wherein the program-related information coordinated with at least one of the channel
numbers relates to a processing program which can be executed by said receiver.

23. (Previously Presented) The program execution method according to claim
20, wherein said electronic apparatus includes:

a communication section for connecting said electronic apparatus to a
communication network,

wherein the program-related information coordinated with at least one of the
channel numbers relates to a program to be executed to allow at least said electronic apparatus to
transmit or receive information through said communication section.

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

24. (Previously Presented) The program execution method according to claim 20, wherein said electronic apparatus includes:

a communication section for connecting said electronic apparatus to a communication network; and

a received information memory for storing received information received through said communication section, and the program-related information coordinated with at least one of the channel numbers relates to a program to be executed to cause at least the received information stored in said received information memory to be outputted.

25. (Previously Presented) The program execution method according to claim 20, wherein said electronic apparatus includes:

a communication section for connecting said electronic apparatus to a communication network; and

a transmission information memory for storing transmission information to be transmitted through said communication section, and the program-related information coordinated with at least one of the channel numbers relates to a program to be executed to cause at least the transmission information stored in said transmission information memory to be outputted.

26. (Previously Presented) The program execution method according to claim 20, wherein said electronic apparatus includes:

a display information memory for storing display information,

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

wherein the program-related information coordinated with at least one of the channel numbers relates to a program to be executed to cause at least the display information stored in said display information memory to be outputted.

27. (Previously Presented) The program execution method according to claim 20, further comprising the steps of:

accepting a display instruction input of a list of the information stored in said predetermined memory; and

forming, when an instruction to display the list is accepted in said instruction input acceptance step, a displaying signal for displaying a list of the information stored in said memory on a display element.

28. (Previously Presented) The program execution method according to claim 27,

wherein said electronic apparatus includes a display element and touched position detection device provided on a display screen of said display element for detecting a touched position of the display screen touched by a user, said program execution method further comprising:

an operation input acceptance step of accepting an operation input from a user through said touched position detection device, a channel number which corresponds to a display item of the list displayed at the touched position of the display screen accepted in the instruction input acceptance step being used as a channel number selected by the user.

U.S. Appl. No. 09/911,186
Reply to Office Action dated July 3, 2006

PATENT
450100-03320

29. (Original) The program execution method according to claim 20, wherein, in the program execution step, the program is executed from a process which was being executed upon switching from a channel number to which the program is allocated to another channel number.